

IN THE CLAIMS:

Please amend claims 1-4, and 6, and add new claims 7-12 as follows:

1. (Currently Amended) A display control apparatus comprising:

a video memory for storing color data, which are used to designate colors for displayed dots, palette data for use in conversion of the color data and address data representing addresses of the color data and the palette data;

a first video memory controller for reading the palette data from the video memory in accordance with the address data, so that read palette data are written to a color palette memory;

a second video memory controller for reading the color data from the video memory in accordance with the address data, so that read color data are subjected to conversion on the color palette memory in accordance with the palette data; and

an output circuit for outputting either the color data read from the video memory or converted color data output from the color palette memory to a display,

wherein if present address data designating present palette data match with previous address data designating previous palette data, the first video memory controller does not write the present palette data to the color palette memory, and wherein if present address data designating present palette data does not match with previous address data designating previous palette data, the first video memory controller writes the present palette data to replace the content of the color palette memory.

2. (Currently Amended) A display control apparatus comprising:

a video memory for storing color data, which are used to designate colors for displayed dots, palette data for use in conversion of the color data and address data

representing addresses of the color data and the palette data;

a first video memory controller for reading the palette data from the video memory in accordance with the address data, so that read palette data are written to a color palette memory;

a second video memory controller for reading the color data from the video memory in accordance with the address data, so that read color data are subjected to conversion on the color palette memory in accordance with the palette data; and

an output circuit for outputting either the color data read from the video memory or converted color data output from the color palette memory to a display,

wherein at completion of writing the previous palette data to the color palette memory, the first video memory controller retains the previous address data designating the previous palette data in a register, ~~so that~~ the first video memory controller determines whether to replace content of the color palette memory by comparison between the present address data and the previous address data such that if present address data designating present palette data matches with previous address data designating previous palette data, the first video memory controller does not write the present palette data to the color palette memory.

3. (Currently Amended) A display control apparatus comprising:

a video memory for storing color data, which are used to designate colors for displayed dots, a color palette replacer instruction, palette data for use in conversion of the color data and address data representing addresses of the color data and the palette data;

a first video memory controller for reading the palette data from the video

memory in accordance with the address data, so that read palette data are written to a color palette memory;

a second video memory controller for reading the color data from the video memory in accordance with the address data, so that read color data are subjected to conversion on the color palette memory in accordance with the palette data; and

an output circuit for outputting either the color data read from the video memory or converted color data output from the color palette memory to a display,

wherein if present address data designating present palette data match with previous address data designating previous palette data, the first video memory controller does not write the present palette data to the color palette memory, if the color palette replacer instruction designates the color palette replacement, the first video memory controller proceeds to ~~replacement of~~ replace the content of the color palette memory unconditionally, regardless of the present or previous address data.

4. (Currently Amended) A display control apparatus comprising:

a video memory for storing display data that contain header data, palette data and bitmap data in connection with a plurality of planes which are combined together to form one frame ~~of picture~~, wherein the header data contain a color palette pointer and a color palette replacer instruction with respect to each of the planes;

a color palette memory for storing color palettes with respect to the plurality of planes;

a video memory controller for reading the palette data and the bitmap data from the video memory in accordance with addresses designated by the header data; and

a color palette replacer signal generator for generating a color palette replacer

signal based on the header data so as to make determination whether to replace content of the color palette with respect to each of the planes,

wherein if the color palette replacer instruction designates color palette replacement, the video memory controller unconditionally replaces previous palette data with present palette data on the color palette memory, while if the color palette replacer instruction does not designate color palette replacement, the video memory controller replaces the previous palette data with the present palette data on the color palette memory only when a present color palette pointer designating the present palette data differs from a previous color palette pointer designating the previous palette data.

5. (Original) A display control apparatus according to claim 4 wherein the header data contain a bitmap data format representing a format of the bitmap data with respect to each of the planes, so that the bitmap data are converted to RGB color data on the color palette memory in response to the bitmap data format.

6. (Currently Amended) A display control apparatus comprising:

a video memory for storing color data, which are used to designate colors for displayed dots, a color palette replacer instruction, palette data for use in conversion of the color data and address data representing addresses of the color data and the palette data;

a first video memory controller for reading the palette data from the video memory in accordance with the address data, so that read palette data are written to a color palette memory;

a second video memory controller for reading the color data from the video

memory in accordance with the address data, so that read color data are subjected to conversion on the color palette memory in accordance with the palette data; and

an output circuit for outputting either the color data read from the video memory or converted color data output from the color palette memory to a display,

wherein at completion of writing the previous palette data to the color palette memory, the first video memory controller retains the previous address data designating the previous palette data in a register, ~~so that~~ the first video memory controller determines whether to replace content of the color palette memory by comparison between the present address data and the previous address data such that if present address data designating present palette data match with previous address data designating previous palette data, the first video memory controller does not write the present palette data to the color palette memory, and if the color palette replacer instruction designates the color palette replacement, the first video memory controller proceeds to ~~replacement of~~ replace the content of the color palette memory unconditionally, regardless of the present or previous address data.

7. (New) A display control apparatus comprising:

a video memory for storing color data, which are used to designate colors for displayed dots, a color palette replacer instruction, a bitmap data format indicator, palette data for use in conversion of the color data and address data representing addresses of the color data and the palette data;

a first video memory controller for reading the palette data from the video memory in accordance with the address data, so that read palette data are written to a color palette memory;

a second video memory controller for reading the color data from the video memory in accordance with the address data, so that read color data are subjected to conversion on the color palette memory in accordance with the palette data; and

an output circuit for outputting either the color data read from the video memory or converted color data output from the color palette memory to a display,

wherein if the color palette replacer instruction designates the color palette replacement and the bitmap data format indicator indicates the color data includes color codes, the first video memory controller proceeds to replace the content of the color palette memory unconditionally, regardless of a present address data or a previous address data.

8. (New) A display control apparatus according to claim 7, wherein if the bitmap data format indicator indicates the color data includes Red Blue Green (RGB) color data, the first video memory controller does not write the present palette data to the color palette memory,

9. (New) A display control apparatus according to claim 7, wherein if the color palette replacer instruction does not designate the color palette replacement and if a transfer complete flag (CPF) indicates the present palette data has been transferred to the color palette memory to form previous palette data, wherein if present address data designating present palette data match with previous address data designating previous palette data, the first video memory controller does not write the present palette data to the color palette memory, and wherein if present address data designating present palette data does not match with previous address data designating previous palette data, the first video memory controller writes the present palette data to replace the

content of the color palette memory.

10. (New) A display control apparatus according to claim 7, wherein if the color palette replacer instruction does not designate the color palette replacement and if a transfer complete flag (CPF) does not indicate the present palette data has been transferred to the color palette memory, the first video memory controller writes the present palette data to replace the content of the color palette memory.

11. (New) A display control apparatus according to claim 7, wherein the color palette replacer instruction, a transfer complete flag, and the bitmap data format indicator are input into a combination of logic gates, and the present address data designating present palette data and the previous address data designating previous palette data are input into a comparison circuit whose output is input to the combination of logic gates to effect a result of the combination of logic gates.

12. (New) A display control apparatus according to claim 11, wherein the combination of logic gates includes AND gates, OR gates, and inverters.

---